



MARKING :

350MHz (UL) E305668 TYPE CM 24AWG 75°C  
 C(UL) E305668 CM 75°C ETL VERIFIED ANSI/TIA-568.2-D  
 UTP CAT.5E RoHS COMPLIANCE MSL-VN- BATCH NO.

8148	
P1	P2
1	1 WHITE/ORANGE
2	2 ORANGE
3	3 WHITE/GREEN
6	6 GREEN
4	4 BLUE
5	5 WHITE/BLUE
7	7 WHITE/BROWN
8	8 BROWN

NOTE: All relevant materials are complied with RoHS directive .

3	MOLDED PVC BLACK	H1BP01-0304K07		M304
2	4 TWISD PAIRS CAT.5E 24AWG(7/0.19AS) UTP, OD 5.3mm, JACKET BLACK, DRAWING No. EU002404P-174	H5AH21-0304K07	L+10mm	M304
1	8P8C MODULAR PLUG, GOLD PLATING 50u" ON CONTACTS, SHORT TYPE	A1NA42-0209	2	M209
No.	DESCRIPTION		Q'TY	Supplier
APPROVED		<b>C5MB-XX</b>		Cable Length Unless Other Spec. Tolerances: 0 ~200mm ±10mm 201~1000mm ±20mm 1001 ~1500mm ±25mm 1501~2100mm ±30mm 2100mm± ±40mm
CHECKED	HU			
DESIGNER	XJW			
DRAWING	WEI			
DATE	14/MAR/23	ITEM NO.		UNIT:mm

CHECKED