



PIN ASSIGNMENT:

P1	P2	P3
1	1	
2		1
3	2	2 SHELL

CUSTOMER P/N	length
FE-3MM-MRCA-04IN	4(IN)100MM ± 20MM
FE-3MM-MRCA-01	1.5(FT)450MM ± 30MM
FE-3MM-MRCA-02	2(FT)605MM ± 30MM
FE-3MM-MRCA-03	3(FT)910MM ± 30MM
FE-3MM-MRCA-06	6(FT)1830MM ± 50MM
FE-3MM-MRCA-12	12(FT)3670MM ± 50MM
FE-3MM-MRCA-20	20(FT)6100MM ± 150MM
FE-3MM-MRCA-25	25(FT)7620MM ± 200MM
FE-3MM-MRCA-35	35(FT)10670MM ± 250MM
FE-3MM-MRCA-50	50(FT)15240MM ± 300MM

NOTES:

- 100% OPEN & SHORT TESTING
- VOLTAGE: 300V DC
- INSULATION RESISTANCE: 20M ohm
- CONTACT RESISTANCE: 1 ohm

9		
8		
7		
6		
5		
4	PVC45Pa	BLACK, RED, WHITE
3		RCA MALE
2		3.5 STEREO TRS MALE
1		NO-UL 28# {(7/0.12CCS)*1C+D}*2F D:2.7*5.4MM BLACK
NO.	Material	Description

MY CABLE MART LLC

Title: AUDIO CABLE			
Customer:	Page: 1/1	Drawn BY: CLR	
Customer P/N:	REV: A	Check BY: DYH	
Date: 2016. 11. 28	Drawing NO. : FVSR21	Unit: mm	Appd BY: