



- NOTES:
- 100% OPEN & SHORT TESTING
 - VOL TAGE: 300V DC
 - INSULATION RESISTANCE: 20M ohm
 - CONTACT RESISTANCE: 1 ohm

CUSTOMER P/N	length
FE-C5S-6IN-BLU	6(IN)150MM ± 20MM
FE-C5S-01-BLU	1(FT)305MM ± 20MM
FE-C5S-02-BLU	2(FT)600MM ± 20MM
FE-C5S-03-BLU	3(FT)915MM ± 30MM
FE-C5S-04-BLU	4(FT)1220MM ± 30MM
FE-C5S-05-BLU	5(FT)1520MM ± 30MM
FE-C5S-06-BLU	6(FT)1830MM ± 40MM
FE-C5S-07-BLU	7(FT)2130MM ± 50MM
FE-C5S-10-BLU	10(FT)3050MM ± 50MM
FE-C5S-14-BLU	14(FT)4270MM ± 80MM
FE-C5S-25-BLU	25(FT)7620MM ± 100MM
FE-C5S-35-BLU	35(FT)10670MM ± 150MM
FE-C5S-40-BLU	40(FT)12200MM ± 160MM
FE-C5S-50-BLU	50(FT)15250MM ± 200MM
FE-C5S-60-BLU	60(FT)18300MM ± 250MM
FE-C5S-75-BLU	75(FT)22870MM ± 300MM
FE-C5S-100-BLU	100(FT)30480MM ± 400MM
FE-C5S-200-BLU	200(FT)61000MM ± 500MM

8		
7		
6		
5		
4		PE BAG+LABEL
3		60Pa BLUE PVC
2		RJ45 8P8C CONN. PIN G/F WITH SHELL
1		CAT5e STP CABLE 26AWG(7/0.16CCA)*4P+AL B(16/5/0.12MM) BLUE OD: 5.5MM
NO.	Material	Description

MY CABLE MART LLC

Title: CAT5e STP CABLE RJ45 M/M			
Customer: MY CABLE MART LLC	Page: 1/1	Drawn BY: CLR	
Customer P/N:	REV: A1	Check BY: DYH	
Date: 2022.05.21	Drawing NO.: FRJU45	Unit: mm	Appd BY: