



AL+MY:5*(8+1)al/my/my
 insulation:5pairs,FPE,OD:Ø0.75±0.02
 conductor:5Cx30AWG(0.25Cu)x1 pair)
 DRAIN:5Cx30AWG(0.25Cu)
 conductor:4Cx30AWG(0.25Cu)
 insulation:4core,OD:Ø0.6±0.03,
 HDPE(1 twisted)
 AL/MY:AL/MY,0.025*30mm
 DRAIN:16/6/0.12AL
 jacket:Ø5.5±0.15mm
 UL PVC,75P,black

HDMI	Signal Assignment	HDMI D
1 Red		Red 3
2 Earth		Earth 4
3 White		White 5
4 Blue		Blue 6
5 Earth		Earth 7
6 White		White 8
7 Green		Green 9
8 Earth		Earth 10
9 White		White 11
10 Brown		Brown 12
11 Earth		Earth 13
12 White		White 14
14 Black		Black 2
17 White		White 16
19 Yellow		Yellow 1
13 Green	CEC	Green 15
15 Orange	SCL	Orange 17
16 Purple	SDA	Purple 18
18 Red	+5 Volts Power	Red 19

FE-HHD14-6IN 150MM(6IN)+/-20MM
 FE-HHD14-01 450MM(1.5FT)+/-30MM
 FE-HHD14-03 900MM(3FT)+/-30MM
 FE-HHD14-06 1830MM(6FT)+/-30MM
 FE-HHD14-10 3050MM(10FT)+/-50MM

5	HDMI Cable	1PCS	
4	TYPE D(P) PLUG GOLD	1SET	
3	TYPE D(P) MOLD	1SET	
2	TYPE A(P) MOLD	1SET	
1	HDMI TYPE A PLUG GOLD	1SET	
NO.	DRAW	SPEC	QTY
DES.		MTL	MDL
CHK.		TRL	PDT
APPR.		QTY	VER
MY CABLEMART LLC		A-1	SCL
Unit: MM		Page 1	Pages 3
		Drw. NO.	

R41.54