



NOTES:
 1.100%OPEN&SHORT TESTING
 2.VOLTAGE:300V DC
 3.INSULATION RESISTANCE:20M ohm
 4.CONTACT RESISTANCE:1 ohm

CUSTOMER P/N	length
FE-USB-CA-6IN	6(IN)155MM ± 15MM
FE-USB-CA-01	1.5(FT)900MM ± 20MM
FE-USB-CA-02	2(FT)4570MM ± 30MM
FE-USB-CA-03	3(FT)4570MM ± 50MM
FE-USB-CA-06	6(FT)4570MM ± 50MM
FE-USB-CA-10	10(FT)4570MM ± 50MM

8		
7		
6		PE BAG+LABEL
5		PCV45Pa Black
4		PE
3		USB CM 56KΩ
2		USB2.0 AM
1		USB2.0 cable 28AWG(7/0.12BC)*1P+24AWG(7/0.2BC) *1C+AL+D(7/0.12BC) OD: 3.0mm Black
NO.	Material	Description

MY CABLE MART LLC

Title: USB2.0 CABLE AM TO CM			
Customer: MY CABLE MART LLC	Page: 1/1	Drawn BY: CLR	
Customer P/N:	REV: A	Check BY: DYH	
Date: 2019.05.20	Drawing NO.: FUAC01	Unit: mm	Appd BY: