



ELECTRICAL TESTING:
 (1)100% open short &miss wire test.
 (2)Insulation Resistance:5MΩ.
 (3)Contact Resistance:5 Ω .
 (4)Dielectric Strength:DC 300V/0.1s.
 (5)HDTV-DVD(1080P):100%.Testing Line Process.

| | | | | | |
|-----|--------------|--|------|------|-------|
| ⑦ | OUTER MOLDED | 45P Black PVC | g | 47 | |
| ⑥ | SHELL | HDMI Shell,Black ABS | PCS | 1 | |
| ⑤ | SHELL | DP Shell,Black ABS | PCS | 1 | |
| ④ | INNER MOLDED | PE | g | 10 | |
| ③ | CON | HDMI AM,Gold Plated Connector + Chip | PCS | 1 | |
| ② | CON | DP/M Gold Plated Connector | PCS | 1 | |
| ① | CABLE | (32AWG*1P+AL)*4P+(32AWG)*6C+D+AL+Black PVCOD:5.0mm | PC | 1 | |
| NO. | ITEM | DESCRIPTION | UNIT | Q'TY | Notes |

| | | | |
|-----------|-----------------|----------------|-----------------|
| Client NO | GC-DPHH-01 | GC-DPHH-06 | GC-DPHH-10 |
| Length | 458±20mm(1.5FT) | 1830±30mm(6FT) | 3050±50mm(10FT) |

| | | | | | | | | | |
|----------|----|----------------------------|------------|----------|----------|-------------|-----|-----------------------|----------------|
| | | <h1>MY CABLE MART LLC</h1> | | | | | | | |
| X.±0.20 | | | | | | Drawing No. | | JXD-DP1024/G/BK/32AWG | |
| .X±0.15 | | | | | | REV | A/O | Title | DP M - HDMI AM |
| .XX±0.10 | | Scale | / | Customer | 1-39 | Checked | | | |
| Page 1/1 | | Item No. | - | Sales | | | | | |
| Unit | mm | Date | 2021/10/27 | | Approval | | | | |