



8	7	6	5	4	3	2	1
				REV.	DESCRIPTION	DATE	DESIGN

PIN Assignment

1	1
3	3
5	5
4	4
6	6
2	2
7	7
9	9
11	11
10	10
12	12
8	8
14	14
19	19
17	17
13	13
15	15
16	16
18	18
SHELL	SHELL

- NOTES:**
- Test Condition:
 - 100% OPEN & SHORT TEST;
 - Insulation Resistance: DC300V 5MΩ(Min) ;
 - Conductor Resistance: 5Ω/Max.
 - Hi-Pot:DC 300V/0.1s.
 - The product is ROHS compliant.
 - HDTV-DVD TEST:4K@60HZ
 - PASS 18G.

Client NO	GC-HH14-01	GC-HH14-03	GC-HH14-06	GC-HH14-10
Length	458±20mm(1.5FT)	915±20mm(3FT)	1830±30mm(6FT)	3050±50mm(10FT)

⑥	COPPER FOIL	copper foil 6*30mm	PCS	2	
⑤	OUTER MOLDED	45P Black PVC	g	12	
④	INNER MOLDED	PE	g	8	
③	SHIELD	HDMI AM shielding Case	PCS	2	
②	CON	HDMI AM Gold Plated Connector	PCS	2	
①	CABLE	[(30AWG+FPE)*1P+D+HDPE+AL-foil]*5P+ (30AWG+HDPE)*4C+AL+AEB+Black PVC OD6.0mm	PC	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes

		MY CABLE MART LLC							
X.±0.20						Drawing No.	JXD-HD1120/G/BK/30AWG/2.0V		
.X±0.15							REV	A/0	Title
.XX±0.10		Scale	/	Customer	1-39	Checked			
		Page	1/1	Item No.	-	Sales			
		Unit	mm	Date	2021/10/26	Approval			