



印字白色: High Speed HDMI® Cable with Ethernet E358026 AWM STYLE 20276 80°C 30V VW-1

PIN Assignment

1		1
3		3
5		5
4		4
6		6
2		2
7		7
9		9
11		11
10		10
12		12
8		8
14		14
19		19
17		17
13		13
15		15
16		16
18		18
SHELL		SHELL

- NOTES:**
- Test Condition:
 - 100% OPEN & SHORT TEST;
 - Insulation Resistance: DC300V 5MΩ(Min) ;
 - Conductor Resistance: 5Ω/Max.
 - Hi-Pot:DC 300V/0.1s.
 - The product is ROHS compliant.
 - HDTV-DVD TEST:4K@60HZ
 - PASS 18G.

Client NO	GC-HH14-01	GC-HH14-03	GC-HH14-06
Length	458±20mm(1.5FT)	915±20mm(3FT)	1830±30mm(6FT)

⑥	COPPER FOIL	copper foil 6*30mm			
⑤	OUTER MOLDED	45P Black PVC	g	12	
④	INNER MOLDED	PE	g	8	
③	SHIELD	HDMI AM shielding Case	PCS	2	
②	CON	HDMI AM Gold Plated Connector	PCS	2	
①	CABLE	[(30AWG+FPE)*1P+D+HDPE+AL-foil]*5P+ (30AWG+HDPE)*4C+AL+AEB+Black PVC OD6.0mm	PC	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes

		<h1>MY CABLE MART LLC</h1>							
X.±0.20						Drawing No.		JXD-HD1120/G/BK/30AWG/2.0V	
.XX±0.15						REV	A/O	Title	HDMI AM-AM
.XX±0.10		Scale	/	Customer	1-39	Checked			
Page 1/1		Item No.	-	Sales					
Unit	mm	Date	2021/06/07	Approval					