



8	7	6	5	4	3	2	1	
				REV.	DESCRIPTION		DATE	DESIGN

PIN Assignment

1	1
3	3
5	5
4	4
6	6
2	2
7	7
9	9
11	11
10	10
12	12
8	8
14	14
19	19
17	17
13	13
15	15
16	16
18	18
SHELL	SHELL

- 1. Test Condition:**
 (1) 100% OPEN & SHORT TEST;
 (2) Insulation Resistance: DC300V 5MΩ(Min) ;
 (3) Conductor Resistance: 20Ω/Max.
 (4) Hi-Pot:DC 300V/0.1s.
2. The product is ROHS compliant.
3. HDTV-DVD TEST:4K@60HZ

Client NO	GC-HH26-40	GC-HH26-50
Length	12200±120mm(40FT)	15240±150mm(50FT)

⑤	OUTER MOLDED	45P Black PVC	g	20	
④	INNER MOLDED	PE	g	10	
③	CON	HDMI AM Gold Plated Connector,with IC-HT8181	PCS	1	
②	CON	HDMI AM Gold Plated Connector	PCS	1	
①	CABLE	[(26AWG+FPE)*1P+D+HDPE+AL-foil]*5P+(28AWG+HDPE)*4C+AL+AEB+Black PVC OD8.0mm	PC	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes

		MY CABLE MART LLC			
.XX±0.10		Drawing No.	JXD-HD1120/G/BK/26AWG+IC		
REV	A/O	Title	HDMI AM-AM	Draw	Song
Scale	/	Customer	1-39	Checked	
Page	1/1	Item No.	-	Sales	
Unit	mm	Date	2021/10/27	Approval	