



PIN Assignment

USB2.0 CM	USB2.0 AM
GND A1,B1,A12,B12,SHELL	4 GND
VBUS A4,B4,A9,B9	1 VBUS
CC A5	
Dp1 A6 UTP_Dp	3 USB D+
Dn1 A7 UTP_Dn	2 USB D-

NOTES:

1. Test Condition:
 - (1) 100% OPEN & SHORT TEST;
 - (2) Insulation Resistance: DC 300V 5MΩ(Min) ;
 - (3) Conductor Resistance: 5Ω/Max.
2. ROHS compliant

客户型号	GC-USB-CA-6IN	GC-USB-CA-12IN	GC-USB-CA-01	GC-USB-CA-02	GC-USB-CA-03
产品长度L	153±20mm(6inch)	305±20mm(12inch)	458±20mm(1.5FT)	610±20mm(2FT)	920±20mm(3FT)
客户型号	GC-USB-CA-06	GC-USB-CA-10	GC-USB-CA-12	GC-USB-CA-15	
产品长度L	1830±30mm(6FT)	3050±50mm(10FT)	3660±50mm(12FT)	4580±50mm(15FT)	

NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes
⑤	OUTER MOLDED	45P Black PVC	g	16	
④	INNER MOLDED	PE	g	10	
③	CON	USB 2.0 Type CM Connector,Nickel Plated	PCS	1	
②	CON	USB 2.0 AM Connector,Nickel Plated	PCS	1	
①	CABLE	(7C/0.12BC+PVC 0.75)*2C(WH,GR)+(11C/0.16BC+PVC 0.95)*1C (RD)+D11C/0.16BC+AL+PVC Black OD:3.0	PC	1	

		MY CABLE MART LLC			
.XX±0.10		Drawing No.		JXD-UC1038/NI/BK	
REV	A/O	Title	USB AM-Type C M	Draw	Song
Scale	/	Customer	-	Checked	
Page	1/1	Item No.	-	Sales	
Unit	mm	Date	2021/10/27	Approval	