



REV.	DESCRIPTION	DATE	DESIGN
------	-------------	------	--------

NOTES:

- Test Condition:
 - 100% OPEN & SHORT TEST;
 - Insulation Resistance: DC 300V 5MΩ(Min) ;
 - Conductor Resistance: 5Ω/Max.
- ROHS compliant

SIGNAL	P1(USB-C)	WIRE COLOR	P2(USB-C)	AWG	SIGNAL
GND	A1,B1,A12,B12		A1,B1,A12,B12	Braid	GND
Vbus	A4,B4,A9,B9		A4,B4,A9,B9	24AWG	Vbus
CC	A5		A5	32AWG	CC
D+	A6		A6	32AWG	D+
D-	A7		A7	32AWG	D-
SSTX1+	A2		B11	32AWG	SSRX1+
SSTX1-	A3		B10	32AWG	SSRX1-
SSRX1-	B10		A3	32AWG	SSTX1-
SSRX1+	B11		A2	32AWG	SSTX1+
Shield	Shell	Braid	Shell	AWG	Shield

Client NO	GC-USB35-CC-01	GC-USB35-CC-03	GC-USB35-CC-06
Length	305±20mm(1FT)	915±20mm(3FT)	1830±30mm(6FT)

MY CABLE MART LLC					
X.±0.20		Drawing No. JXD-UC1114/NI/BK			
.X±0.15		REV	A/O	Title	USB 3.0 AM-Type C M
.XX±0.10		Scale	/	Customer	1-39
		Page	1/1	Item No.	-
		Unit	mm	Date	2022/04/28
				Draw	Song
				Checked	
				Sales	
				Approval	

④	OUTER MOLDED	45P Black PVC			
③	INNER MOLDED	PE			
②	CON	USB 3.0 Type CM Connector,Nickel Plated	PCS	2	
①	CABLE	(7/0.08TA*1PR+AL)*1P+7/0.08TA*4C+41/0.08TA*2C+#112/0.08TA+Black PVC OD 4.5mm	PCS	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes