



REV.	DESCRIPTION	DATE	DESIGN
------	-------------	------	--------

**PIN Assignment**

USB2.0 CM	USB2.0 AM
GND A1,B1,A12,B12,SHELL	GND 4 GND
VBUS A4,B4,A9,B9	Vbus 1 VBUS
CC A5	R56K
Dp1 B5	R56K
Dn1 A6 UTP_Dp	3 USB D+
A7 UTP_Dn	2 USB D-

**NOTES:**

1. Test Condition:  
 (1) 100% OPEN & SHORT TEST;  
 (2) Insulation Resistance: DC 300V 5MΩ(Min) ;  
 (3) Conductor Resistance: 5Ω/Max.
2. ROHS compliant
3. Quick charge

Client	GC-USBQC-CA-6IN	GC-USBQC-CA-12IN	GC-USBQC-CA-015	GC-USBQC-CA-02	GC-USBQC-CA-03	GC-USBQC-CA-06
Length	153±20mm(6inch)	305±20mm(12inch)	458±20mm(3FT)	610±20mm(2FT)	915±20mm(3FT)	1830±20mm(6FT)

⑤	OUTER MOLDED	45P Black PVC	g	16	
④	INNER MOLDED	PE	g	10	
③	CON	USB 2.0 Type CM Connector,Nickel Plated	PCS	1	
②	CON	USB 2.0 AM Connector,Nickel Plated	PCS	1	
①	CABLE	(10/0.10TC+PVC 0.75)*1P(WH,GR)+(64C/0.10TC+TPEE 1.4)*2C (RD,BK)+D64C/0.10TC+AL+PVC Black OD:4.0	PC	1	
NO.	ITEM	DESCRIPTION	UNIT	Q'TY	Notes

		MY CABLE MART LLC			
.XX±0.10		Drawing No. JXD-UC1038/NI/BK			
REV	A/O	Title	USB AM-Type C M	Draw	Song
Scale	/	Customer	1-39	Checked	
Page	1/1	Item No.	-	Sales	
Unit	mm	Date	2021/06/07	Approval	